

MEB210 Series

Lightweight, Molded Accelerometer, 100 mV/g Top Exit, Integral Cable, 10-32 Mounting, General Purpose



A CTC DIVISION
PROTECTION & RELIABILITY INSTRUMENTS




Product Features

- ▶ Overmolded Accelerometer
- ▶ IP68 Rated
- ▶ Low Cost

MEB210

Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	MEB210	MEB220	Environmental		
Sensitivity ($\pm 10\%$)		100 mV/g	Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response ($\pm 3\text{dB}$)	30-900,000 CPM	0.5 Hz-15 kHz	Maximum Shock Protection		10,000 g, peak
Frequency Response ($\pm 10\%$)	60-600,000 CPM	1 Hz-10 kHz	Electromagnetic Sensitivity		CE Pending
Dynamic Range		$\pm 50\text{g}$, peak	Sealing		Welded, Hermetic
Electrical			Physical		
Settling Time		< 2 Seconds	Sensing Element		PZT Ceramic
Voltage Source (IEPE)		18-30 VDC	Sensing Structure		Shear Mode
Constant Current Excitation		2-10 mA	Weight	0.35 oz	10 grams
Spectral Noise @ 10 Hz		30 $\mu\text{g}/\sqrt{\text{Hz}}$	Case Material		316L Stainless Steel
Spectral Noise @ 100 Hz		4 $\mu\text{g}/\sqrt{\text{Hz}}$	Mounting		10-32 UNF
Spectral Noise @ 1000 Hz		2 $\mu\text{g}/\sqrt{\text{Hz}}$	Connector		10-32
Output Impedance		< 100 ohm	Cable Jacket Diameter		0.14 in (3.6 mm)
Bias Output Voltage		10-14 VDC	Cable Jacket Material		Polyurethane
Case Isolation		> 10^8 ohm	Cable Conductor		26 AWG Twisted Shielded Pair
			Resonant Frequency	2,640,000 CPM	44 kHz
			Mounting Hardware	10-32 Stud	M5 Stud
			Calibration Certificate		CA10

Typical Frequency Response



Lifetime Warranty on Materials & Workmanship

www.ctconline.com | sales@ctconline.com | 585-924-5900