



## **Extraneous Load Factors**

**Equation:**  $\sigma_{\text{max}} \ge (A)Fx + (B)Fy + (C)Fz + (D)Mx + (E)My + (F)Mz$ 





Material: 2024-T4 Aluminum (AL\*)

Material	Capacity (lb)	A	В	C	D	E	F
	5	100.76	1764.76	2645.43	1674.91	841.65	2076.97
	10	65.80	1240.98	1259.06	764.11	765.20	1494.24
(AL*)	25	45.34	774.75	592.35	534.04	697.58	946.04
(AL)	50	35.91	589.02	348.14	434.03	786.87	699.50
	100	27.70	430.99	198.74	562.96	784.22	510.59
	150	36.90	362.86	155.05	770.10	936.77	496.65

## $\sigma_{ m max}$ Table

Material	Static Load (=60% Y.S.)	Fatigue (Non Reversing Loads)	Fatigue (Full Reversing Loads)	
2024-T4/T351	28,000	18,000	15,000	

<sup>\*</sup>Value is 75% of Fatigue Strength based on  $10\text{-}20 \times 10^6$  cycles and allow for factors that influence Fatigue such as surface finish, stress concentrations, corrosion, temperature and other variables for the production of the transducer, for infinite Fatigue Life ( $100 \times 10^6$ ) use 75% of values shown.

## **Deflection & Natural Frequency**

Material	Capacity (lb)	Deflection (in.)	Natural Frequency (Hz)	β
	5	0.0028	1,500	0.0074
	10	0.0026	2,300	0.0073
(AL*)	25	0.0023	3,800	0.0072
(AL)	50	0.0026	5,100	0.0072
	100	0.0028	7,100	0.0070
	150	0.0032	8,100	0.0071

<sup>\*</sup>FN results are based on calculation of deflection & weight scene on Sensor arm.

This documentation was generated and completed to the best ability of FUTEK's Engineering Team using FEA Analysis, Empirical data and Multiple Testing Simulations. The information and recommendations on this document are presented in good faith and believed to be correct however, FUTEK Advanced Sensor Technology makes no representations or warranties as to the completeness or accuracy of the information.



## Natural Frequency & Frequency Response Equation's:

Natural Frequency (FN) = 
$$3.13 \sqrt{\frac{1}{\frac{\beta}{Capacity}} \bullet Deflection}}$$
 (Hz)

Frequency Response with load (FR) = 
$$3.13 \sqrt{\frac{1}{\frac{\beta + AppliedLoad}{Capacity}} \bullet Deflection}}$$
 (Hz)

\*Where eta values are obtained by Futek Engineers